

10.11.2022

Product Datasheet
fiber optic cable: InAir ADSS 2kN

Order information		
Design	Part number	
InAir ADSS 12 Ultra 2kN 0.327	548434	
InAir ADSS 24 Ultra 2kN 0.327	548439	
InAir ADSS 36 Ultra 2kN 0.327	548444	
InAir ADSS 48 Ultra 2kN 0.327	548447	
InAir ADSS 72 Ultra 2kN 0.327	548452	
InAir ADSS 96 Ultra 2kN 0.378	554444	
InAir ADSS 144 Ultra 2kN 0.480	548502	

Other fiber counts available upon request

Typical application and features

- Aerial installation between poles and buildings
- Aerial installation on powerlines
- Aerial installation for communication lines
- Pulling into underground ducts and sewer pipes
- Installation along bridges, tunnels and other structures
- Installation into indoor/outdoor cable conduits and trays




All-dielectric design




UV-resistant

Design



Cable consists of stranded core with central strength member (FRP), gel-filled loose tubes with optical fibers and PE fillers. Stranded core is fixed by water-swellable yarns. Aramid yarns are laid over stranded core. Outer jacket is made of MDPE. Two ripcords are laid under outer jacket.

Optical fibers and loose tubes color identification:



Other colors upon request

Cable marking example

Marking is made on each 2 feet of cable

00001 FT	= INCAB	OPTICAL CABLE =	PART NUMBER	InAir ADSS	48	Ultra	2kN	0.327		2022
1	2		3	4	5	6	7	8		9
1	Length marking unit			6	Fiber type					
2	Manufacturer			7	Maximum rated design tension					
3	Part number			8	Diameter					
4	Cable trade name			9	Year of production					
5	Fiber count									

Additional information upon request. Marking can also be in meters

Design details

Fiber count		12	24	36	48	72	96	144
Number of loose tubes		1	2	3	4	6	8	12
Fibers per loose tube		12						
Number of PE fillers		5	4	3	2	-	-	-
Loose tube diameter	in (mm)	0.079 (2.0)						
Outer jacket thickness	in (mm)	0.039 (1.0)						
Cable diameter ± 0.008 (0.2)	in (mm)	0.327 (8.3)			0.378 (9.6)		0.480 (12.2)	
Cable weight	lb/ft (kg/km)	0.034 (50.3)			0.044 (65.0)		0.074 (110.2)	
Maximum rated design tension	lb (kN)	450 (2.0)						
Zero fiber strain margin	lb (kN)	202 (0.9)						
Stringing tension (STT)	lb (kN)	112 (0.5)						
Rated breaking strength (RBS)	lb (kN)	1192 (5.3)			1147 (5.1)		2338 (10.4)	
Modulus of elasticity, initial	ksi (kN/ mm ²)	889 (6.13)			634 (4.37)		808 (5.57)	
Modulus of elasticity, final	ksi (kN/ mm ²)	960 (6.62)			685 (4.72)		872 (6.02)	
10-year modulus of elasticity, creep	ksi (kN/ mm ²)	693 (4.78)			494 (3.41)		630 (4.34)	
Cable cross-sectional area	in ² (mm ²)	0.084 (53.9)			0.112 (72.3)		0.182 (117.3)	
Coefficient of thermal expansion, 10 ⁻⁶	1/°F (1/°C)	7.48 (13.47)			9.24 (16.63)		7.55 (13.59)	

Other design upon request

Operating parameters

Operation temperature range	-40°F...+158°F	-40°C...+70°C
Installation temperature range	-22°F...+122°F	-30°C...+50°C
Transportation and storage temperature range	-58°F...+158°F	-50°C...+70°C
Minimum bending radius, with load	15 x cable diameter	
Minimum bending radius, with no load	10 x cable diameter	
Design life	25 years (per fiber supplier)	

Reel capacity

Standard maximum reel length*	20,000 ft	6,100 m
-------------------------------	-----------	---------

* Longer length may be possible

Performance standard

Complies with IEEE 1222-2019 requirements

Optical fiber

Fiber type	«Ultra»
Product name	Corning SMF 28® ULTRA
ITU-T Recommendation	G.652D + G.657.A1
Transmission Specifications	
Attenuation in the cable (dB/km)*:	
1310 nm wavelength (Typical** / Max.)	0.32 / 0.34
1550 nm wavelength (Typical** / Max.)	0.19 / 0.20

* Local attenuation discontinuities caused by cable winding on a reel are allowed

** Typical attenuation is the real level of optical attenuation of at least 90% fibers after cabling

Additional information about optical fiber at www.incabamerica.com

Reel packing and marking

Cables are supplied on non-returnable wooden reels. Reel diameter is not less than 40 diameters of the cable. Not less than 2 m of inside end of the cable is fixed to the reel flange. The cable ends are sealed with waterproof covers. The label on the outer reel flange contains our trademark, cable type, customer's name and PO, reel number, production date, cable length, cable weight net/gross.

The following information is printed on the reel flange: manufacturer's name and website, rotation direction, cable end indication, shipping and handling summary, labels "Fragile" and "Handle with care".

Our cable passport shows: cable type, technical standard number, cable length, fiber type, fiber coloring, fibers per tube, tube identification coloring, final attenuation for all fibers, refractive index of the fiber, fiber manufacturer and production date.

Cable passport is affixed to the inner flange in a plastic bag. Additional information can be included on the passport upon request.

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Incab America LLC can take no responsibility for actions taken based on the information contained in this document. Incab America reserves the right to make changes to this document without notice. All sales of product are subject to Incab America's terms and conditions of sale only, which can be found on the website www.incabamerica.com. This document is protected by copyright (c) of Incab America LLC. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Incab America will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.