

Product Datasheet
fiber optic cable InSky OPGW S 96U (4x24) 13.5mm 57kA2-s 69kN

Order information

Design

InSky OPGW S 96U (4x24) 13.5mm 57kA2-s 69kN

Part number

0113-70325

Features



ACS wires are highly corrosion-resistant




Aluminum alloy wires provide conductivity for fault current



Optical ground wire shields high-voltage conductors from lightning strikes

Design



Design element	Material	Count	Diameter	
			Metric (mm)	Customary (inches)
Center member	AY wire	1	2.70	0.1063
1st stranded layer	20% ACS wire/SSLT	2/4	2.70	0.1063
2nd stranded layer	20% ACS wire/AY-wire	6/6	2.70	0.1063

Technical Specifications

Mechanical	Metric	Customary
Cable diameter ± 0.2 mm (0.008 in)	13.5 mm	0.531 in
Cable unit weight	475 kg/km	0.319 lb/ft
Rated breaking strength (RBS) (without SSLT's)	69.1 kN	15 532 lb
Maximum rated design tension (MRDT) (80% RBS) with 0% fiber strain	54.6 kN	12 277 lb
Zero fiber strain margin (ZFSM) (80% RBS)	54.6 kN	12 277 lb
Cross-sectional area of ACS wire	51.8 mm ²	0.080 in ²
Cross-sectional area of AY-wire	40.08 mm ²	0.062 in ²
Cable total cross-sectional area	91.9 mm ²	0.142 in ²
Modulus of Elasticity, initial	86.9 kN/mm ²	12 606 ksi
Modulus of Elasticity, final	109.8 kN/mm ²	15 928 ksi
Temperature coefficient of linear expansion	15.42 E ⁻⁶ /°C	8.56 E ⁻⁶ /°F
Southwire Sag10™ coefficient chart number	1-420	-
Lay direction of outer layer	Left	-

Electrical	Metric	Customary
DC resistance at 20°C (68°F)	0.557 Ω /km	0.8968 Ω /mile
Short circuit capacity	56.9 kA ² ·s	-
Basis: Initial cable temp = 40°C (104°F), Final = 210°C (410°F), Duration = 0.5 s		
Short current circuit for 0.5 s	10.7 kA	-
Rac/Rdc ratio	1.012	-
AC resistance at 25°C (77°F)	0.5736 Ω /km	0.9231 Ω /mile
AC resistance at 50°C (122°F)	0.6233 Ω /km	1.0030 Ω /mile
AC resistance at 75°C (167°F)	0.6730 Ω /km	1.0830 Ω /mile
Geometric Mean Radius (GMR)	2.2488 mm	0.0074 ft
Inductive Reactance (Xa) @ 60 Hz	0.3702 Ω /km	0.5957 Ω /mile
Capacitive Reactance (X'a) @ 60 Hz	0.1819 M Ω -km	0.1130 M Ω -mile

Optical		
ITU-T fiber compliance		G.652D & G.657.A1
Fiber manufacturer		Corning SMF-28 ULTRA
Fiber count (Actual/Maximum)		96/96
Fibers per SSLT		24

Color identification of loose tubes / optical fibers is according to ANSI/TIA-598-D-2014



Color identification of the binding yarns for bundles 1-2 of 12 fibers:



Color identification of SSLT's:



Other colors upon request

Fiber Dimensional Specifications:	
Core-Clad Concentricity	$\leq 0.5 \mu\text{m}$
Cladding Diameter	$125 \pm 0.7 \mu\text{m}$
Cladding Non-Circularity	$\leq 12 \mu\text{m}$
Coating Diameter	$242 \pm 5 \mu\text{m}$

Final Maximum Individual Attenuation Limits:	
Wavelength	dB/km
1310 nm	0.34
1383 nm	0.34
1490 nm	0.23
1550 nm	0.20
1625 nm	0.22

Reel Packing and Handling	Metric	Customary
Maximum reel length	5 980 m	19 619 ft
Minimum bending radius, no load (tension < 5% RBS)	203 mm	8 in
Minimum bending radius, loaded (tension ≥ 5% RBS)	229 mm	9 in
Standard sheave diameter: first, last, angles ≥ 60°	584 mm	23 in
Standard sheave diameter: tangents and angles ≤ 60°	381 mm	15 in

Operating parameters	Metric	Customary
Operation temperature	-50°C ... +85°C	-58°F ... +185°F
Installation temperature	-30°C ... +50°C	-22°F ... +122°F
Transportation and storage temperature	-50°C ... +70°C	-58°F ... +158°F
Life time	50 years	

Standards	International	USA
ACS wire	IEC 61232	ASTM B415
AY wire	IEC 60104	ASTM B398
OPGW cable	IEC 60794	IEEE 1138

Key Performance Testing		
Parameter	Nominal value	Evaluation criterion
Strain margin test (IEEE 1138-2009 p.6.4.1.3.)	54.6 kN	$\Delta\alpha^* < 0.20$ dB/test fiber km; - no damage
Crush (IEEE 1138-2009 p.6.4.2.2.)	1.0 kN/cm	$\Delta\alpha^* < 0.05$ dB/ fiber; - no damage
Twist (IEEE 1138-2009 p.6.4.2.4.)	2 cycles @ twist angle $\pm 90^\circ$ per 1 m	$\Delta\alpha^* < 0.10$ dB/test fiber km
Water ingress test (IEEE 1138-2009 p.6.4.3.5.)	1 m for 1 hours	No water through end of cable
Temperature cycling** (IEEE 1138-2009 p.6.4.3.7.)	-50°C to +85°C for 2 cycles over ≥ 16 hours	$\Delta\alpha^* < 0.20$ dB/test fiber km
Seepage of flooding compound (IEEE 1138-2009 p.6.4.3.6.)	65°C	No dripped compound

* - attenuation increase at standard wavelengths

** - other temperature range upon request

Reel Packing and Marking Notes

- Standard packing is non-returnable wooden reels
- Reel diameter ≥ 40 x cable OD
- ≥ 2 m of inside end of cable is affixed to flange
- Cable ends are sealed with waterproof covers
- Label on the outer flange of the reel contains the following information:
cable type, customer's name and PO, reel number, production date, cable length, cable weight net/gross
- Flange marking includes: manufacturer's name and website, rotation direction, cable end indication, shipping and handling summary, labels "Fragile" and "Handle with care"
- A Cable Passport is attached to each reel and provides the following information:
cable type, technical standard number, cable length, fiber type, fiber coloring, fibers/tube, tube identification coloring, final attenuation for all fibers, refractive index of the fiber, fiber manufacturer and production date
- Each Cable Passport is affixed to the inner flange. Additional information can be included on the Cable Passport upon request

All values are nominal and are subject to normal manufacturing tolerances and to change without notice